



BUILDING SHELL TECHNOLOGY










Rotary mixer POX-S

For mixing small volumes with ease



With Collomix at the pool position

-  Handy and portable mixers with a permanently fixed mixing mechanism and rotating mixing tub
-  Mixing action via rotating tub
-  Edge and bottom scraper prevents sediment collecting on the edges of the container
-  Compact design and light weight allow high labor mobility
-  For the bucket transportation a dolly is available as accessory
-  Suitable for compact and plastic mortar, screed, plaster with aggregate and lean concrete
-  The practical helper for mason, composition floor layer, garden designers and landscapers, renovators

Screed



Plaster



Drainage mortar



Universal mortar




Concrete



Synthetic resin screed



Material (weight without added water):	POX
Slightly moist concrete with grain size of -16 mm (30 l)	+
Concrete with max. grain size of 16 mm (30 l)	+
Cement screed (35 l)	+
Universal mortar (40 l)	+
Synthetic resin screed	+
Light wall mortar (25 l)	+
Cement stucco (40 l)	+
Gypsum plaster (40 l)	-
Loam plaster without fiber (40 l)	-
Heat-insulating plaster (30 l)	+
Mortar for natural stone slabs (30 l)	+
2-component slab pointing mortar (-1,2 mm, 30 l)	+
Middle-bed mortar (25 l)	-
Tile adhesives (flexible mortar, 25 l)	-
Pointing mortar (25 l)	-
Flowing screed (40 l)	-
Thin-bed mortar, cement for concrete precision blocks (30 l)	-
Creamy types of plaster (40 l)	-
Adhesive grouting compounds as backing for plaster (30 l)	-
Tile adhesives (25 l)	-
Pointing mortar (25 l)	-
Joint sealing compound (30 l)	-
2-component sealing grouting compounds (25 l)	-
Leveling compounds (25 l)	-
2-component epoxy-resin and sand mix (30 l)	-



Mixing tool POX-S



Accessory Trolley



Delivery



Productfilm

MADE IN GERMANY



TECHNICAL DATA:

Mixing volume:	max. 40 litres	Item no. POX-S:	37124
Size of mixing tub:	65 litres	Item no. mixing tool	70190
Power rating of tube drive:	0,75 kW / 230 V	Accessory	
RPM of tube drive:	50 rpm	Item no. mixing tub 65 l:	60403
Weight:	48 kg	Item no. trolley 65 l tube:	70183
Dimensions:	60 x 82 x 77 cm		



Collomix GmbH
Daimlerstraße 9
85080 Gaimersheim
Germany

Tel: +49 8458 32 98 0
Fax: +49 8458 32 98 30
Email: info@collomix.de
Web: www.collomix.de

Your Collomix dealer: