

... powerful

Compulsory mixers

100 - 240 litres mix

... easier to operate.

- vertical adjustment
- removable hand draw bar





sturdy
powerful
economical
time-tested





Compulsory mixers

for comfortable working with maximum ease of operation



TECHNICAL DETAILS:			
	ZM 100	ZM 200	ZM 300
Capacity			
Mixer drum	200 l	280 l	340 l
Ready mix*	100 l	180 l	240 l
Discharge height	530 – 680 mm	530 – 680 mm	530 – 680 mm
Drive	4,0 kW	5,5 kW	7,5 kW
Dimensions L	1400 mm	1400 mm	1450 mm
W	1200 mm	1200 mm	1250 mm
Н	1100 mm	1100 mm	1100 mm
Weight	210 kg	380 kg	460 kg
Electric	Motor-protection switch with		
equipment	preselection of sense of rotation		
	coupler socket 16 A/32 A		
Safety	Automatic switch-off when opening		
equipment	protective grating.		
	Discharge protection		
	EC and GS approved		
Accessories	Dome for drum		
	Turbo cyclone		

Reserve made to technical modifications

* depending on material and weight

VARIANTS AVAILABLE:

- **▶** stationary
- ▶ movable with hand draw bar
- ▶ road version 80 km/h
- ▶ electric motion/Diesel drive
- ▶ special-purpose designs by request

UEZ compulsory mixers are rapidly performing the mixing proces in an intensive and homogeneous manner!

All kinds of concretes, refractory masses, floor pavements, epoxy, steel-chip reinforced concrete, granulates, mortar, clay, terrazzo, chamotte a.s.o...

Features

UEZ-<u>four-arms mixing technique</u> assures intensive mixing within short time.

<u>Mixer arms spring-cushioned</u> – mixer blades made of high-quality working material.

<u>Low pour-in height</u> due to vertical adjustment.

<u>Compact and sturdy design</u> assures secure standing.

The hand draw bar and the two solid tyres allow easy movement of the mixer. Removable hand draw bar saves cost of transportation.

<u>Powerful</u> drive system. No maintenance required.

<u>Long life</u> – high-quality materials have gone into construction.

Reversing motor-protection switch with plug box 16 A/32 A and preselector of sense of rotation.

Mixing process can be watched easily because of exposed mixer drum.

Rapid and clean evacuation.

<u>Segmental discharge slide</u> on drum bottom allows dosing of mix discharge.

The protective grate cover of the drum (with bag opener) is hinged and equipped with automatic switch-off device.

Rapid transportation from one building site to the other due to 80 km/h road version (trailer coupling for car and truck).

CE-conform.

UEZ Michtechnik GmbH

Röntgenstraße 5-7 · D-73730 Esslingen Phone +49 (0) 711 - 3180971 Fax +49 (0) 711 - 3180268 www.uez-mischer.de · info@uez-mischer.de