

Serial heating unit series WMO-R4

for operating temperatures up to 450°C



- bank unit with four heating positions for flasks, round bottom
- flexible glass yarn heating element
an even heat transfer and a gentle treatment of the glassware
- each heating position with built-in controller
allows a continuous adjustment of power outlet
- plastic-coated metal housing
characterised by a chemical-resistant metal housing providing excellent stability
- thermally insulated and earthed
- predrilled threaded hole on rear allows to fix the clamp HM-SK (accessories) for each position
- with residual current detection (RCD)
- **CE**
our heating mantles perform the requirements based on the European harmonized standards



Technical specification

WMO-R4

Nominal voltage	230 V AC
Nominal power output	see ordering details
Heating zones	see ordering details
Safety class	I
System of protection	casing IP 43, heating surface IP 00
Heating element temperature	max. 450°C
Power supply cable	1,5 m with schuko-plug (earthed) and RCD switch

Ordering details

Volume ml	Flask Ø mm	Power W	Heating zone	Dimensions B x H x T mm	Part.-No.
4 x 100	4 x 64	4 x 110	1	580 x 150 x 290	83400100
4 x 250	4 x 85	4 x 220	1	580 x 150 x 290	83400250
4 x 500	4 x 105	4 x 330	1	580 x 150 x 290	83400500
4 x 1000	4 x 131	4 x 495	1	580 x 150 x 290	83401000

Accessories

Support clamp type HM-SK	Part.-No. 97000001
to fix support rods with diameter up to Ø 13 mm each position	