

## Pallet scale KERN UFN



## Pallet scale with stainless steel load support (IP67) and stainless steel display device (IP65), with EC type approval [M]

### Features

- High mobility: thanks to rechargeable battery operation, compact, lightweight construction, it is suitable for the use in several locations (production, warehouse, dispatch department etc.)
- **1** Load support: stainless steel, Weighing bridge can also be delivered as component without the display device, for details see KERN KFU-V30
- 4 silicone-coated steel load cells, dust and spray protection IP67
- Your support in a HACCP-compliant quality system
- Ideal for the increased hygienic requirements in the food industries
- **2** Display device: for details see KERN KFN-TM
- The scale can be easily transported using rollers and a handle and does not require much storage space
- Hold function: When the weighing conditions are unstable, a stable weight is calculated determining an average value

- Weighing with tolerance range (checkweighing): A visual and audible signal assists the rapid checking of items on pallets
- Totalising of weights
- **3** Did you know? Our floor scales are delivered in a robust wooden box. This protects the high-quality weighing technology from environmental influences and stresses during transportation. KERN – always one step ahead

### Technical data

- Large backlit LCD display, digit height 52 mm
- Dimensions of display device WxDxH 266x165x96 mm
- Cable length of display device approx. 5 m
- Permissible ambient temperature -10 °C/40 °C

### Accessories

- **4** Stand to elevate display device, height of stand approx. 800 mm, KERN BFN-A04
- Internal rechargeable battery pack, operating time up to 35 h without backlight, charging time approx. 10 h, KERN GAB-A04
- RS-232 data interface including interface cable, Data interface RS-232, interface cable included, approx. 1,5 m, must be ordered at purchase, KERN KFN-A01
- Bluetooth data interface for wireless data transfer to PC or tablets, must be ordered at purchase, not possible in combination with verification, KERN KFB-A03
- Analogue module 0-10 V, must be ordered at purchase, KERN KFB-A04
- Analogue module 4-20 mA, must be ordered at purchase, KERN KFB-A05
- Large display with superior display size, KERN YKD-A02
- Cable with special length 15 m, between display device and platform, for verified models which must be ordered at the time of purchase, KERN BFB-A03
- Further details, plenty of further accessories and suitable printers see *Accessories*

**1** Shipment via freight forwarder. Please ask for dimensions, gross weight, shipping costs  
Optionally configurable with IP68 display device on request, for details see chapter 13


### STANDARD



### OPTION



### FACTORY



Model	Weighing capacity [Max] kg	Readability = Verification value [d] = [e] kg	Verification value [e] kg	Minimal load [Min] kg	Net weight approx. kg	Verification M KERN	Option DAkKS Calibr. Certificate DAkKS KERN
<b>KERN UFN 600K200IPM</b>	600	0,2	0,2	4	55	965-230	963-130
<b>KERN UFN 1.5T0.5IPM</b>	1500	0,5	0,5	10	50	965-230	963-130

Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible.  
Verification at the factory, we need to know the full address of the location of use.

- 
**Internal adjusting:**  
 Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)
- 
**Network interface:**  
 For connecting the scale to an Ethernet network
- 
**Suspended weighing:**  
 Load support with hook on the underside of the balance
- 
**Adjusting program CAL:**  
 For quick setting up of the balance's accuracy. External adjusting weight required
- 
**KERN Communication Protocol (KCP):**  
 It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems
- 
**Battery operation:**  
 Ready for battery operation. The battery type is specified for each device
- 
**Easy Touch:**  
 Suitable for the connection, data transmission and control through PC or tablet.
- 
**Rechargeable battery pack:**  
 Rechargeable set
- 
**Memory:**  
 Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.
- 
**GLP/ISO log:**  
 The balance displays weight, date and time, independent of a printer connection
- 
**Universal plug-in power supply:**  
 with universal input and optional input socket adapters for  
 A) EU, CH, GB  
 B) EU, CH, GB, USA  
 C) EU, CH, GB, USA, AUS
- 
**Alibi memory:**  
 Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.
- 
**GLP/ISO log:**  
 With weight, date and time. Only with KERN printers.
- 
**Plug-in power supply:**  
 230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available
- 
**KERN Universal Port (KUP):**  
 allows the connection of external KUP interface adapters, e.g. RS-232, RS-485, SB, Bluetooth, WLAN, Analogue, Ethernet etc. for the exchange of data and control commands, without installation effort
- 
**Piece counting:**  
 Reference quantities selectable. Display can be switched from piece to weight
- 
**Integrated power supply unit:**  
 Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request
- 
**Data interface RS-232:**  
 To connect the balance to a printer, PC or network
- 
**Recipe level A:**  
 The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out
- 
**Weighing principle: Strain gauges**  
 Electrical resistor on an elastic deforming body
- 
**RS-485 data interface:**  
 To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible
- 
**Recipe level B:**  
 Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display
- 
**Weighing principle: Tuning fork**  
 A resonating body is electromagnetically excited, causing it to oscillate
- 
**USB data interface:**  
 To connect the balance to a printer, PC or other peripherals
- 
**Totalising level A:**  
 The weights of similar items can be added together and the total can be printed out
- 
**Weighing principle: Electromagnetic force compensation**  
 Coil inside a permanent magnet. For the most accurate weighings
- 
**Bluetooth\* data interface:**  
 To transfer data from the balance to a printer, PC or other peripherals
- 
**Percentage determination:**  
 Determining the deviation in % from the target value (100 %)
- 
**Weighing principle: Single cell technology:**  
 Advanced version of the force compensation principle with the highest level of precision
- 
**WiFi data interface:**  
 To transfer data from the balance to a printer, PC or other peripherals
- 
**Weighing units:**  
 Can be switched to e.g. nonmetric units. See balance model. Please refer to KERN's website for more details
- 
**Verification possible:**  
 The time required for verification is specified in the pictogram
- 
**Control outputs (optocoupler, digital I/O):**  
 To connect relays, signal lamps, valves, etc.
- 
**Weighing with tolerance range:**  
 (Checkweighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model
- 
**DAkkS calibration possible (DKD):**  
 The time required for DAkkS calibration is shown in days in the pictogram
- 
**Analogue interface:**  
 to connect a suitable peripheral device for analogue processing of the measurements
- 
**Hold function:**  
 (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value
- 
**Factory calibration (ISO):**  
 The time required for Factory calibration is shown in days in the pictogram
- 
**Interface for second balance:**  
 For direct connection of a second balance
- 
**Protection against dust and water splashes IPxx:**  
 The type of protection is shown in the pictogram.
- 
**Package shipment:**  
 The time required for internal shipping preparations is shown in days in the pictogram
- 
**Pallet shipment:**  
 The time required for internal shipping preparations is shown in days in the pictogram

\*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.