

## **ZM 50**



## Small powerful compulsory mixer

- 16 mm grains
- Throrough mixing
- UEZ 3-arms mixing technique
- Discharge through bottom
- Variable in height
- Universal use
- Solid and compact design
- CE and GS approved

ZM 50 is a powerful, handy mixer. The UEZ 3-arms mixing technique having been most successful in thousands of applications assures steady and thorough mixing within very short time. Materials can be added easily just to the mixing drum. The mixing process can be well watched, as the mixing drum is accessible.

During the mixing operation, you may add easily any further bulk goods required. For adding binders, a bag opener is attached to the protective grate.

A segmental discharge slide on the drum bottom allows dosing of mix discharge.

ZM 50 can be moved easily without great effort on the two solid rubber tyres. Some suitable lugs are attached for handling by crane. The solid and compact version

TECH	NICAL DETAILS:
Capacity	Mixing drum 95 I
Ready mix	Depending on consistency/
	material approx. 60 l
Grain	max. 16 mm at drive 2.2 kW/
	400V
Discharge	Trough segmental slide in
	bottom
Mixing	UEZ 3-arms mixing technique
apparatus	with wall wiper, reinforced mixer
	with wall wiper for 16 mm grains
Drive	230 V 1.5 kW A. C.
	400 V 2.2 kW 3 phases A. C.
Speed	Mixing apparatus 58 rpm
Electrics	230 V motor-protection switch
	with plug socket
	400 V with preselection of sense
	of rotation
Design	Mobile, height adjustable
Tyres	2 solid-rubber tyres
Safety	Automatic switch-off when
equipment	opening protective grating.
	Other safety equipement to EU
	standards CE and GS approved
Dimensions	L 750 mm, W 600 mm, H 1030 mm
Weight	80 kg

Reserve made to technical modifications

is designed for severe everyday construction-site service. Its quality, workmanship and successful drive elements assure long life.



Fine concrete · refractory masses liquide synthetics · insulating materials epoxy mortar · cast plaster floors terrazzo · chamotte cement

## **UEZ MISCHTECHNIK**

Röntgenstrasse 5-7 · 73730 Esslingen

Telephone: 0049 - 711 - 3180971 and 3161104

Telefax: 0049 - 711 - 3 18 02 68